



## MOUNTING SUGGESTIONS

### Kawasaki Vulcan 2000 2004-2010 Solo and Passenger Seat

**Hardware:** Stock 6mm bolt x2  
White nylon washer x

**Tools needed:** 8mm wrench

#### Removal of stock seat:

1. Remove the right seat cover with the ignition key, locate and pull the passenger seat release cable. Slide passenger seat forward and lift off the motorcycle.
2. Remove the two 6mm hex bolts mounting the solo to the fender. These will be used to install your new Mustang seat.
3. Lift the solo up and slide back to remove. Replace the right-side cover.



## **Installation of Mustang seat:**

1. Slide the solo's front bracket under the frame bracket at the base of the fuel tank.
2. Position the white nylon washers between the solo brackets and the fender and secure the solo to the fender using the stock 6mm bolts.
3. Slide the passenger seat back into the fender's U-bracket and push firmly until it clicks, signifying the seat is latched into position. Ensure this bracket is firmly engaged before riding.

**Enjoy the comfort and custom look of your new Mustang seat!**



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 8:30 - 5:00 Eastern or send an e-mail to [tech@mustangseats.com](mailto:tech@mustangseats.com) or visit our website at [www.mustangseats.com](http://www.mustangseats.com).

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 76490, 76491, 76492, 76493, 76494, 76495, 79370, 79371, 79372, 79373, 79374, 79375



**Products made by Mustang Motorcycle Products, LLC are warranted for one year against defects in material and workmanship. Mustang must first be notified of any apparent defect. A return authorization will be issued. Carefully pack the product and return prepaid. Upon receipt, Mustang will make a fair, prompt decision regarding repair or replacement.**

**Incidental and consequential damages arising from or in connection with the installation or use of a Mustang product are not covered by this warranty. An original purchase receipt must be provided to obtain a warranty repair or replacement.**