



MOUNTING SUGGESTIONS

Kawasaki Vulcan 800 1996-2005 One-piece Seat

Hardware: Stock 6mm rear bolt
White nylon washer

Tools needed: Metric socket and Allen wrenches

Removal of stock seat:

1. Remove rear 6mm bolt and set aside. This bolt will be used to mount your new Mustang seat.

2. Slide the seat back and up to remove.
Note: The seat is often very tight, some force may be necessary.

3. Remove the center bracket from the fender and re-install the two bolts into the fender.



Installation of Mustang seat:

1. Engage the front bracket into the frame receptacle under the tank.
2. Position the white nylon washer between the rear bracket and the fender hole and secure the seat with the stock 6mm bolt.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 8:30 - 5:00 Eastern or send an e-mail to tech@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 75919, 75930, 75933, 76338



Products made by Mustang Motorcycle Products, LLC are warranted for one year against defects in material and workmanship. Mustang must first be notified of any apparent defect. A return authorization will be issued. Carefully pack the product and return prepaid. Upon receipt, Mustang will make a fair, prompt decision regarding repair or replacement.

Incidental and consequential damages arising from or in connection with the installation or use of a Mustang product are not covered by this warranty. An original purchase receipt must be provided to obtain a warranty repair or replacement.