



MOUNTING SUGGESTIONS

Suzuki M50 2005-2011 Solo and Passenger Seat

<u>Hardware:</u>	<u>Solo:</u>	<u>Passenger:</u>
	Chrome stud bracket White nylon washer Slotted nut	Stock rear fender screw

Tools needed: Metric Allen wrench
5/8" wrench

Removal of stock seat:

1. Remove the rear Allen screw.
This will be used to mount your new Mustang seat.
2. Slide the passenger seat back to remove.
3. Remove the rear seat mounting bracket and hand strap.
4. Slide solo back and up to remove.



Installation of Mustang seat:

1. Install the stud bracket to the fender. The stud must be toward the back of the motorcycle. (If missing, this bracket is available as part 78122.)
2. Engage the solo's nose bracket into frame receptacle below tank. Place the nylon washer over the stud, lower the rear solo bracket over the stud, and secure with the slotted nut. **Note: do not overtighten.**
3. Engage the passenger seat's slotted front bracket with the slotted nut.
4. Secure the rear bracket with the stock screw.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 8:30 - 5:00 Eastern or send an e-mail to tech@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 76590, 76591, 76592, 76593, 76594, 76595, 79540, 79541, 79542, 79543, 79544, 79545



Products made by Mustang Motorcycle Products, LLC are warranted for one year against defects in material and workmanship. Mustang must first be notified of any apparent defect. A return authorization will be issued. Carefully pack the product and return prepaid. Upon receipt, Mustang will make a fair, prompt decision regarding repair or replacement. Incidental and consequential damages arising from or in connection with the installation or use of a Mustang product are not covered by this warranty. An original purchase receipt must be provided to obtain a warranty repair or replacement.