



MOUNTING SUGGESTIONS

Suzuki VZ800 Marauder 1997-2004 Solo and Passenger Seat

Hardware: Passenger seat:
Stock 8mm rear bolt
Stock 6mm front bolt x2

Tools needed: Metric Allen wrenches

Removal of stock seat:

1. Insert the ignition key into the lock on left side cover and turn to unlock the seat.
2. Pull the nose of the solo up and slide it forward to remove.
3. Remove the two Allen bolts from the front of the passenger seat and the Allen bolt at the back of the passenger seat and set aside. These will be used to mount your Mustang passenger seat.
4. Lift passenger seat from fender to remove.



Installation of Mustang seat:

1. Position the passenger seat on the fender and mount with the stock 8mm Allen bolt at the back and the stock 6mms at the front.
2. Slide the solo's rear bracket into the fender mount. Check to be certain the seat skirt is not tucked under the seat and interfering with install.
3. Pivot the seat down until the front bracket engages the frame latch and a click is heard. Ensure this latch is secure before riding.

Enjoy the comfort and custom look of your new Mustang seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392 or 413-668-1100, Monday through Friday 8:30 - 5:00 Eastern or send an e-mail to tech@mustangseats.com or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Refers to part numbers: 75818, 75825, 75826



Products made by Mustang Motorcycle Products, LLC are warranted for one year against defects in material and workmanship. Mustang must first be notified of any apparent defect. A return authorization will be issued. Carefully pack the product and return prepaid. Upon receipt, Mustang will make a fair, prompt decision regarding repair or replacement.

Incidental and consequential damages arising from or in connection with the installation or use of a Mustang product are not covered by this warranty. An original purchase receipt must be provided to obtain a warranty repair or replacement.